



Technical Data Sheet

Model MS 802-4

Housing material		Aluminum
Phase		Three
Frame size		80
Power(50Hz)	kW	0.75
Current(A)230V	Δ	3.21
Current(A)400V	Y	1.85
Speed(50Hz)	(r/min)	1390
Efficiency	IE1	
	Eff.100%	74.40
	Eff.75%	76.00
	Eff.50%	73.90
Power factor cosφ	100% load	0.79
60Hz 265/460V	Power(kW)	0.86
60Hz 276/480V	Power(kW)	0.90
Speed(60Hz)	(r/min)	1670
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitute		1000 m above sea level

Rated torque(N.m)	5.15
Tst/Tn (Times)	2.5
Tmax/Tn (Times)	2.55
Tmin/Tn (Times)	2.05
Ist/In (Times)	5.4
Bearings type(DE)	6204-2RZ
Bearings type(NDE)	6204-2RZ
Oil seals	20x34x7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	58
Net weight(kg)	9.10
Moment of inertia (kg*m²)	0.001793119



Bearings & Seals
 Chains & Sprockets
 Electric Motors & Drives
 Belts & Pulleys
 Gearboxes & Couplings
 Lubricants & Tools
 Field Services

Tel: +27 11 899 0000
 Email: info@bearings.co.za
www.bearings.co.za