

ALPHA



Technical Data Sheet

Model T1C 225S-4

| | | |
|--------------------------|-----------|----------------------------|
| Housing material | | Casting iron |
| Phase | | Three |
| Frame size | | 225 |
| Power(50Hz) | kW | 37.00 |
| Current(A)400V | Δ | 65.80 |
| Current(A)690V | Y | 38.14 |
| Speed(50Hz) | (r/min) | 1470 |
| Efficiency | IE1 | |
| | Eff.100% | 91.20 |
| | Eff.75% | 90.90 |
| | Eff.50% | 88.80 |
| Power factor cosφ | 100% load | 0.89 |
| 60Hz 460/793V | Power(kW) | 42.55 |
| 60Hz 480/830V | Power(kW) | 44.40 |
| Speed(60Hz) | (r/min) | 1764 |
| Regulations | | IEC / DIN / ISO / VDE / EN |
| Standard | | IEC 60034 |
| Ambient Temp. | | -20°C ~ +40°C |
| Maximum altitude | | 1000 m above sea level |

| | |
|---|-------------------|
| Rated torque(N.m) | 240.37 |
| Tst/Tn (Times) | 2.2 |
| Tmax/Tn (Times) | 2.6 |
| Tmin/Tn (Times) | 1.3 |
| Ist/In (Times) | 8 |
| Bearings type(DE) | 6313C3 |
| Bearings type(NDE) | 6313C3 |
| Oil seals | 65*90*10 |
| Cable glands | 2-M50*1.5 |
| Insulation class | F |
| Protection degree | IP 55 |
| Thermal protection | Without |
| Rotation direction | Clockwise |
| Service duty | S1 |
| Balance | Half-key balanced |
| Cooling | IC 411 |
| Noise dB(A) | 81 |
| Net weight(kg) | 293.00 |
| Moment of inertia (kg*m²) | 0.504390000 |



- Bearings & Seals
- Chains & Sprockets
- Electric Motors & Drives
- Belts & Pulleys
- Gearboxes & Couplings
- Lubricants & Tools
- Field Services

Tel: +27 11 899 0000
Email: info@bearings.co.za
www.bearings.co.za