



Technical Data Sheet

Model **MS 801-2**

Housing material		Aluminum
Phase		Three
Frame size		80
Power(50Hz)	kW	0.75
Current(A)230V	Δ	3.02
Current(A)400V	Y	1.73
Speed(50Hz)	(r/min)	2830
Efficiency	IE1	
	Eff.100%	75.20
	Eff.75%	75.60
	Eff.50%	72.20
Power factor cosφ	100% load	0.83
60Hz 265/460V	Power(kW)	0.86
60Hz 276/480V	Power(kW)	0.90
Speed(60Hz)	(r/min)	3400
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitude		1000 m above sea level

Rated torque(N.m)	2.53
Tst/Tn (Times)	3
Tmax/Tn (Times)	2.8
Tmin/Tn (Times)	2
Ist/In (Times)	6.2
Bearings type(DE)	6204-2RZ
Bearings type(NDE)	6204-2RZ
Oil seals	20x34x7
Cable glands	1-M20*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	67
Net weight(kg)	8.70
Moment of inertia (kg*m²)	0.000880031



Bearings & Seals
 Chains & Sprockets
 Electric Motors & Drives
 Belts & Pulleys
 Gearboxes & Couplings
 Lubricants & Tools
 Field Services

Tel: +27 11 899 0000
 Email: info@bearings.co.za
www.bearings.co.za