



Technical Data Sheet

Model MS 112M-6

Housing material		Aluminum
Phase		Three
Frame size		112
Power(50Hz)	kW	2.20
Current(A)230V	Δ	8.89
Current(A)400V	Y	5.11
Speed(50Hz)	(r/min)	925
Efficiency	IE1	
	Eff.100%	79.20
	Eff.75%	81.80
	Eff.50%	81.70
Power factor cosφ	100% load	0.78
60Hz 265/460V	Power(kW)	2.53
60Hz 276/480V	Power(kW)	2.64
Speed(60Hz)	(r/min)	1110
Regulations		IEC / DIN / ISO / VDE / EN
Standard		IEC 60034
Ambient Temp.		-20°C ~ +40°C
Maximum altitute		1000 m above sea level

Rated torque(N.m)	22.71
Tst/Tn (Times)	1.9
Tmax/Tn (Times)	2.25
Tmin/Tn (Times)	1.75
Ist/In (Times)	4.7
Bearings type(DE)	6306-2RZ
Bearings type(NDE)	6206-2RZ
Oil seals	30x44x7
Cable glands	2-M25*1.5
Insulation class	F
Protection degree	IP 55
Thermal protection	Without
Rotation direction	Clockwise
Service duty	S1
Balance	Half-key balanced
Cooling	IC 411
Noise dB(A)	64
Net weight(kg)	25.00
Moment of inertia (kg*m²)	0.013776520



Bearings & Seals
 Chains & Sprockets
 Electric Motors & Drives
 Belts & Pulleys
 Gearboxes & Couplings
 Lubricants & Tools
 Field Services

Tel: +27 11 899 0000
 Email: info@bearings.co.za
www.bearings.co.za